

## KIT-XZ20-XKE-H (CS-XZ20XKEW-H + CU-Z20XKE)



[FIND OUT MORE](#)



**Bringing nature's balance indoors**

**nanoe<sup>+</sup>X, technology with the benefits of hydroxyl radicals.**

Abundant in nature, hydroxyl radicals (OH radicals) have the capacity to inhibit pollutants, certain viruses, and bacteria to clean and deodorise.

nanoe<sup>+</sup>X technology can bring these incredible benefits indoors so that hard surfaces, soft furnishings, and the indoor environment can be a cleaner and pleasant place to be, whether at home, at work, or visiting hotels, shops, restaurants etc.

[FIND OUT MORE](#)

**Panasonic Comfort Cloud App. Take control of your comfort**

[FIND OUT MORE](#)





## New Voice Control

Control without boundaries and get hands-free help to fully access the features of your air conditioners.

[FIND OUT MORE](#)



## AC Quick Selector

Helping you to find the Air Conditioning solution for up to five individual rooms, in just a few clicks!

[TRY THE DOMESTIC AIRCON QUICK SELECTOR](#)



## AR Heat Pump Viewer

Interested to see how a Panasonic Air Conditioner looks in your home? Try the new Panasonic AR projector, utilising augmented reality!

[TRY THE AIR CONDITIONER AR HEAT PUMP VIEWER](#)

<b>Etherea with nanoe™ X Graphite grey R32</b>		<b>2.05 kW</b>
Cooling capacity (Min)	kW	0,75
Input power heating (Min)	kW	0,16
COP (Max) (1)	W/W	4,26
COP (Min) (1)	W/W	4,69
Heating capacity (Max)	kW	4,00
Heating capacity (Min)	kW	0,75
Input power cooling (Max)	kW	0,67
Input power cooling (Min)	kW	0,16
EER (Max) (1)	W/W	3,96
EER (Min) (1)	W/W	4,69
Cooling capacity (Max)	kW	2,65
Input power heating (Max)	kW	0,94
Operating range (Heat - Max)	°C	+24
Operating range (Heat - Min)	°C	-15
Operating range (Cool - Max)	°C	+43
Elevation difference (in/out) (6)	m	15
Outdoor dimension (Depth) (5)	mm	289
Outdoor dimension (Width) (5)	mm	780
Outdoor dimension (Height) (5)	mm	542
Outdoor sound pressure (Heat -Hi) (4)	dB(A)	46
Outdoor unit	CU-Z20XKE	
nanoe X Generator	Mark 2	

<b>Etherea with nanoe™ X Graphite grey R32</b>		
		<b>2.05 kW</b>
Outdoor air flow (Heat)	m <sup>3</sup> /min	26,7
Outdoor air flow (Cool)	m <sup>3</sup> /min	27,4
Indoor unit		CS-XZ20XKEW-H
Indoor sound pressure (Heat -Q-Lo) (4)	dB(A)	19
Indoor sound pressure (Heat -Lo) (4)	dB(A)	25
Indoor sound pressure (Heat -Hi) (4)	dB(A)	38
Indoor sound pressure (Cool -Q-Lo) (4)	dB(A)	19
Indoor sound pressure (Cool -Lo) (4)	dB(A)	24
Moisture removal volume	L/h	1,3
Indoor air flow (Heat)	m <sup>3</sup> /min	13,0
Indoor air flow (Cool)	m <sup>3</sup> /min	11,7
Indoor connection indoor / outdoor	mm <sup>2</sup>	4 x 1,5
Indoor power source	V	230
Annual energy consumption heating (3)	kWh/a	613
Annual energy consumption cooling (3)	kWh/a	91
Input power cooling (Nominal)	kW	0,45
Pdesign (cooling)	kW	2,1
SEER (2)		8,10 A++
Outdoor net weight	kg	25
Outdoor sound pressure (Cool -Hi) (4)	dB(A)	45

<b>Etherea with nanoe™ X Graphite grey R32</b>		<b>2.05 kW</b>
Indoor net weight	kg	10
Indoor dimension (Height)	mm	295
Indoor sound pressure (Cool -Hi) (4)	dB(A)	37
SCOP (2)		4,80 A++
Pipe length range	m	3 ~ 15
Heating capacity at -7°C	kW	2,38
Kit		KIT-XZ20-XKE-H
Additional gas amount	g/m	10
Pipe length for additional gas	m	7,5
Pipe diameter (Gas)	Inch (mm)	3/8 (9,52)
Pipe diameter (Liquid)	Inch (mm)	1/4 (6,35)
Indoor dimension (Depth)	mm	229
Indoor dimension (Width)	mm	870
Indoor recommended fuse	A	16
Refrigerant (R32) / CO2 Eq.	kg / T	0,67 / 0,45
EER (Nominal) (1)	W/W	4,56
COP (Nominal) (1)	W/W	4,52
Heating capacity (Nominal)	kW	2,80
Cooling capacity (Nominal)	kW	2,05
Operating range (Cool - Min)	°C	-10
Input power heating (Nominal)	kW	0,62
Pdesign at -10°C	kW	2,1


## Complementary products



CZ-CAPRA1 RAC interface adapter for integration into P Link



PAW-SMSCONTROL. Control by SMS (need additional SIM card).



CZ-RD517C. Wired remote controller for wall-mounted and floor console